

# Mitchell

# MD400

...It's **ELECTRIC!**

The Mitchell MD400 guitars (Modern Double-Cutaway) feature a carved, double-cutaway mahogany body, bound mahogany neck, and an H/Mini-H pickup system. They're spot-on for the modern, heavy and hard rock player looking for a refined, contemporary look and more aggressive sound dynamics.

## BASICS

- Carved mahogany body, off-set double-cutaway design
- Mahogany one-piece set neck
- H/Mini-H rail pickup configuration

## FEATURES AND BENEFITS

- Paraffin-dipped pickups reduce microphonics & feedback
- Stunning multi-ply binding provides eye-catching looks
- Back-angled output jack helps eliminate accidental unplugging
- High-tensile strength fretwire for durability and smooth playability



## HIGHLIGHTS



Rail-style Alnico V pickups reduce tonal dropouts



Deep Bevel Cutaway (DBC) allows complete fretboard access



String-through design and adjustable TOM-style bridge for sustain and solid intonation



Locking tuning machines and Graph Tech™ TUSQ XL reduced-friction nut enhance tuning stability

## MD400 SERIES SPECIFICATIONS

BODY STYLE	Modern Rock Double-Cutaway
BODY MATERIAL	Carved Mahogany
BODY BINDING	Multi-ABS
TUNERS	18:1 Die-Cast Locking
NUT	TUSQ XL™
PICKUP CONFIGURATION	Mini-H, H
Neck Pickup	Mini-Rail Humbucker Alnico V
Middle Pickup	N/A
Bridge Pickup	Rail Humbucker Alnico V
CONTROLS	Vol 1, Vol 2, Master Tone
SWITCHING	3-Way Blade Switch
COIL TAP	Pull Tone Pot (both PU)
BRIDGE	TOM-Style; Strung-Thru Body
HARDWARE	Black Nickel
PICKGUARD	N/A
AVAILABLE FINISHES	Black (BK), Transparent Ocean Blue (TOB), Transparent Purple w/ AAA Quilt Maple Veneer Top (QPR), Transparent Forest Green w/ AAA Quilt Maple Veneer Top (QFG), Natural w/AAA Quilt Maple Veneer Top (QNT)

NECK STYLE	Set-In
NECK SHAPE	Shallow "C"
NECK MATERIAL	Bound Mahogany
NECK FINISH	Body-Matching Gloss Finish
NECK BINDING	Multi-ABS (Cream/Black/Cream)
# OF FRETS	24
FRETWIRE	Tall/Narrow Medium Jumbo
SCALE LENGTH	25.5" (648mm)
RADIUS	400mm (15.75")
WIDTH AT NUT	42mm (1.65")
WIDTH AT LAST FRET	57mm
THICKNESS AT 1ST FRET	22mm
THICKNESS AT 12TH FRET	23mm
FRETBOARD	Indian Rosewood
INLAY	Offset Abalone Dot
TRUSS ROD	2-Way Adjustable (4mm Hex Wrench)